

Appl. No. : 09/651,051
Filed : August 24, 2000

AMENDMENTS TO THE CLAIMS

Amendments to the Claims:

As indicated below, please (i) cancel Claim 13 without prejudice (ii) amend Claims 14-18, 24 and 28 and (iii) add new Claims 29-30. The below listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-13. (Canceled)

14. (Currently amended) A direct fuel injected system as set forth in Claim 17 [13], wherein said fuel pressure sensor is positioned between said fuel pump and said pressure regulator.

15. (Currently amended) A direct fuel injected system as set forth in Claim 18 [13], wherein said fuel system further includes a fuel rail that supplies fuel to said fuel injector and said fuel pressure sensor is connected to said fuel rail downstream of said fuel injector.

16. (Currently amended) A direct fuel injected system as set forth in Claim 18 [13], wherein said vibration damping apparatus includes dampening materials.

17. (Currently amended) A direct fuel injected system for an internal combustion engine having at least one combustion chamber, comprising a high pressure fuel pump for developing high pressure fuel, a fuel injector to directly inject fuel into the combustion chamber of said engine, a pressure regulator to regulate fuel pressure within the fuel system, and a fuel pressure sensor for sensing a fuel pressure of the fuel, said fuel pressure sensor being secured to said engine through a vibration damping apparatus ~~A direct fuel injected system as set forth in Claim 13, wherein said vibration damping apparatus includes a first and a second dampening material, said first dampening material being stiffer than the second dampening material.~~

18. (Currently amended) A direct fuel injected system for an internal combustion engine having at least one combustion chamber, comprising a high pressure fuel pump for developing high pressure fuel, a fuel injector to directly inject fuel into the combustion chamber of said engine, a pressure regulator to regulate fuel pressure within the fuel system, and a fuel pressure sensor for sensing a fuel pressure of the fuel, said fuel pressure sensor being secured to said engine through a vibration damping apparatus ~~A direct fuel injected system as set forth in Claim 13,~~

Appl. No. : 09/651,051
Filed : August 24, 2000

wherein said vibration dampening apparatus includes an electronic control box for housing an electronic control unit.

19. **(Original)** A direct fuel injected system as set forth in Claim 18, wherein said vibration dampening apparatus further includes a fuel injector driver box for housing an injector control unit.

20. **(Original)** A direct fuel injected system as set forth in Claim 19, wherein said pressure sensor is mounted onto said fuel injector driver box.

21. **(Original)** A direct fuel injected system as set forth in Claim 20, wherein said electronic control box is mounted on said engine and is insulated from engine vibrations by a first dampening material.

22. **(Original)** A direct fuel injected system as set forth in Claim 21, wherein said fuel injector driver box is mounted on said electronic control box and is insulated from the vibration of the electronic control box by a second dampening material.

23. **(Original)** A direct fuel injected system as set forth in Claim 22, wherein said first dampening material is stiffer than the second dampening material.

24. **(Currently amended)** A direct fuel injected system for an internal combustion engine comprising a high pressure fuel pump for developing high pressure fuel, a fuel injector to directly inject fuel into a combustion chamber of said engine, a fuel pressure sensor that communicates with said fuel system for measuring a fuel pressure within said fuel system, the fuel pressure sensor being mounted on an electronic control box for housing an electronic control unit and means for protecting the fuel pressure sensor from damage caused by engine vibrations.

25. **(Canceled)**

26. **(Canceled)**

27. **(Canceled)**

28. **(Currently amended)** A direct fuel injected system for an internal combustion engine having at least one combustion chamber, comprising a high pressure fuel pump for developing high pressure fuel, a fuel injector to directly inject fuel into the combustion chamber of said engine, the fuel injector receiving high pressure fuel from the fuel pump, a fuel pressure sensor for sensing a fuel pressure of the fuel, said fuel pressure sensor being secured to said engine through

Appl. No. : 09/651,051
Filed : August 24, 2000

a vibration damping apparatus and a pressure dampening device comprising an elastic conduit in communication with the fuel injector, the elastic conduit having at least one elastic wall exposed to said high pressure fuel without intervening structures.

29. (New) A direct fuel injected system for an internal combustion engine having at least one combustion chamber, comprising a high pressure fuel pump for developing high pressure fuel, a fuel injector to directly inject fuel into the combustion chamber of said engine, the fuel injector receiving high pressure fuel from the fuel pump, and a pressure dampening device in communication with the fuel injector, wherein said pressure dampening device comprises an elastic conduit having at least one elastic wall exposed to said high pressure fuel without intervening structures.

30. (New) A direct fuel injected system as set forth in Claim 29, wherein said elastic conduit comprises an inner member that is made of an elastic material, a middle member made of a material having greater tensile strength than the inner material, and an outer protective member.

31. (New) A direct fuel injected system as set forth in Claim 30, wherein said inner member is made of a rubber.

32. (New) A direct fuel injected system as set forth in Claim 31, wherein said middle member is made of a resin fiber material.

33. (New) A direct fuel injected system as set forth in Claim 32, wherein said outer protective member is made of rubber.

34. (New) A direct fuel injected system as set forth in Claim 29, wherein said fuel system further includes a fuel rail that supplies fuel to said fuel injector and said elastic conduit device supplies fuel to said fuel rail.

35. (New) A direct fuel injected system as set forth in Claim 29, wherein said fuel system further includes a fuel rail that supplies fuel to said fuel injector and said pressure dampening device is connected to an end of said fuel rail downstream of said fuel injector.

36. (New) A direct fuel injected system as set forth in Claim 35, wherein said pressure dampening device is an elastic conduit with a plugged end.

37. (New) A direct fuel injected system as set forth in Claim 29, wherein said engine is enclosed within a protective cowling and includes a vertically disposed crank shaft and two banks

Appl. No. : **09/651,051**
Filed : **August 24, 2000**

of cylinders in a V-type configuration, said fuel system further including a fuel rail that is secured to a cylinder head of each bank of cylinders and said pressure dampening device is connected to at least one end of the fuel rail.

38. (New) A direct fuel injected system as set forth in Claim 37, wherein the pressure dampening device is connected to a lower end of the fuel rail.

39. (New) A direct fuel injected system as set forth in Claim 38, wherein the pressure dampening device is an elastic conduit plugged at one end.